



CWT 1640 Regular



FACTS

PART NO	CWT 164010
CAPACITY UP TO	Up to 140 m ² /h (1500sq. ft./h)
TABLE LENGTH	4000mm (13ft. in.)
TABLE WIDTH	1600mm (5ft. 3in.)
LENGTH OF WORKING AREA	3560mm (11ft. 8in.)
WIDTH OF WORKING AREA/ROLLER WIDTH	1560mm (5ft. 1.5in.)
OVERALL WIDTH	1810mm (5ft. 11 in.)
OVERALL HEIGHT	1620mm (5ft. 4in.)
MAX. THICKNESS OF SUBSTRATE	0-70mm (0-2.8 in.)
WORK HEIGHT	744-950mm (2ft. 5in. - 3ft. 1in.)
WORK HEIGHT ADJUSTEMENT*	Manual
BED SURFACE	Tempered safety glass
POWER SUPPLY**	230V/50Hz (10A) or 120V/60Hz (15A)
REQUIRED AIR SUPPLY	6-8bar (87-116psi)
NET WEIGHT	500kg (1102lbs)
GROSS WEIGHT	655kg (1444lbs)
PACKING DIMENSIONS	4150x560x2300mm (13ft. 8in. x 1ft. 10in. x 7ft. 6in.)
WARRANTY	3 years

FEATURES

CUTTING MAT, SELF HEALING	Yes
LED ILLUMINATED LIGHT TABLE	Option
ROLL HOLDER FOR GUIDE BEAM	Yes
EXTRA LOWER ROLL HOLDER	Option
TABLE TOP ROLL HOLDER	Option
SIDE POCKETS	Yes
SILENT COMPRESSOR	Option
SECOND GLIDE BEAM	Option
WHEELS	Yes
LEVELING FEETS	Yes
PREMIUM UPGRADE KIT***	Option

* Select 1 of 4 fixed heights at installation

** Only when including Premium upgrade kit

*** Premium upgrade kit includes: LED illuminated light table, extra lower roll holder and roll holder for table top

CWT Worktools USA, 8101 Tristar Drive, Suite 110, Irving, TX 75063
Warehouses in Dallas, TX • Logan Township, NJ • Los Angeles, CA

Phone: 469-758-2288 • www.cwtworktoolsusa.com • sales@cwtworktoolsusa.com